



kaleidescape

Kaleidescape M300 Player

KPLAYER-M300

- ▶ **Blu-ray Disc, DVD and CD playback**
- ▶ **High-definition onscreen user interface**
- ▶ **Proprietary M-Class architecture**
- ▶ **Compatible with popular control systems and remote control devices**



The M300 Player's elegant onscreen user interface presents your collection of movies and music with eye-popping detail and beautiful cover art. The exclusive Kaleidescape Movie Guide provides cover art, synopses, and details like actors, directors, genres and ratings. Songs on concert films are indexed for easy access. Movies start instantly, without advertisements, trailers or menus. Press "Play," sit back, and enjoy the feature — even for Blu-ray.

The M300 Player is based on Kaleidescape's M-Class architecture, a powerful platform for the onscreen user interface and for playing

Blu-ray content. Blu-ray movies are played in high definition video with lossless audio, including support for 1080p video with 24 frames per second, and bitstream pass-through of Dolby TrueHD and DTS-HD Master Audio.

An M300 Player can play the copy of a Blu-ray Disc, DVD or CD stored on your server. For Blu-ray, playback must be enabled by the presence of the physical disc in one of your M500 Players.



KPLAYER-M300 Specifications

Dimensions

- 8.4 in. × 1.7 in. × 10.6 in. (W × H × D)
(21.3 cm × 4.3 cm × 26.9 cm)
- Optional rack-mount shelf is available to hold two M300 Players in 1 rack unit

Weight

- 3.0 lbs (1.4 kg)
(includes 1.0 lb (0.5 kg) power supply)
- Rack-mount shelf: 0.5 lbs (0.2 kg)

Power

- 100–240 V, 50–60 Hz universal input
- 28 W typical consumption
(20 W standby, 28 W max)

Network

- 100Base-TX/1000Base-T
Ethernet (RJ45 connector)

Control

- Kaleidescape Remote included
- Front-panel IR receiver window
- IR input (1/8 in. mini-plug)



Environment

- Operating temperature: 41 to 95°F (5 to 35°C)
- Storage temperature: -4 to 140°F (-20 to 60°C)
- Relative humidity: 5 to 90% non-condensing
- Maximum operating altitude: 10,000 ft (3000 m)
- Heat output: 96 BTU/hr (28 W) max
- Airflow: 6 CFM (10 m³/hr) min

Ventilation

- Minimum 1 in. (2.5 cm) ventilation space at the front
- Minimum 2 in. (5 cm) ventilation space at the rear

Video Outputs

- HDMI
- Component YP_bP_r (RCA connectors)
- Composite (RCA connector)

Video Modes

- 1080p60/50/24, 1080i60/50, 720p60/50, 576p, 576i, 480p, 480i

Audio Outputs

- HDMI®
- Digital coaxial (RCA connector)
- Analog stereo (RCA connectors)

Audio Formats

- Bitstream pass-through of Dolby* TrueHD and DTS-HD Master Audio™
- Dolby Digital
- DTS Digital Surround™
- MPEG Audio
- PCM

Blu-ray Disc

- BD-Live
- Profile 2.0

Region Codes

- Blu-ray region code cannot be changed by user
 - ▶ KPLAYER-M500-A (region A)
 - ▶ KPLAYER-M500-B (region B)

Certifications

- CSA (IEC 60950-1:2001, CSA 60950-1-03)
- FCC Class B
- CE
- GOST R
- RoHS compliant



kaleidescape

www.kaleidescape.com

Copyright © 2010 Kaleidescape, Inc. All rights reserved. Kaleidescape and the Kaleidescape logo are trademarks of Kaleidescape, Inc.; they are registered in the United States and certain other jurisdictions. HDMI is a trademark of HDMI Licensing LLC in the United States and other countries. DTS is a registered trademark of DTS, Inc. *Dolby Digital technology and Dolby TrueHD technology. Dolby is a registered trademark of Dolby Laboratories. Other trademarks and trade names are owned by third parties and may be registered in some jurisdictions.